# 57

With unique breather valve to keep balance of the air pressure inside and outside better to ensure IP65 and improve its lifetime



New design with patented removable PIR sensor Free induction distance, Ensure still IP65 when with sensor



Photocell function available





AC DRIVER | 3 YEARS | DIE CASTING | 1P65

S-LITE LED FLOOD LI

01 www.numin.com

## GOOD PRODUCTS ARE DESIGNED

### With unique breather design to keep balance of the air pressure inside&outside

- · Full die casting aluminum housing with good heat dissipation
- ·Ultrathin design to have an elegant appearance
- · High quality PC reflector to achieve wide beam angle and better illumination effect
- · Reliable LED chip with high lumen efficiency
- · Efficient LED driver solution to guarantee a safe and good quality
- · Multi-function to be more options and more competitive
- · 3years warranty
- ·CE,RoHS approval
- ·1P69
- ·With easy and quick installation, widely used in Stadium, Hotel, Advertisement, Park, Plaza...etc



#### Outdoor wall washing

Make the buildings have a good night show and improve the appearance of the city



#### Advertising

High advertising lighting to achieve the effect of night publicity



#### Indoor events

Indoor large events lighting to make it brighter and enhance the atmosphere

Item Code	Voltage	Power (W)	Lumen Efficiency (±10%)	CRI	Power Factor	Beam Angle	IP	Product Size (LxWxH/mm)
01FL-SL-10W	AC200-240V AC110-265V	10W	90lm/w	80	0.5/0.9	120°	65	103x83x24
01FL-SL-20W	AC200-240V AC110-265V	20W	90lm/w	80	0.5/0.9	120°	65	124x100x24
01FL-SL-30W	AC200-240V AC110-265V	30W	90lm/w	80	0.9	120°	65	159x122x26
01FL-SL-50W	AC200-240V AC110-265V	50W	90lm/w	80	0.9	120°	65	205x160x34
01FL-SL-100W	AC200-240V AC110-265V	100W	90lm/w	80	0.9	120°	65	270x210x34
01FL-SL-150W	AC200-240V AC110-265V	150W	90lm/w	80	0.9	120°	65	380x280x46
01FL-SL-200W	AC200-240V AC110-265V	200W	90lm/w	80	0.9	120°	65	380x280x46
01FL-SL-250W	AC200-240V AC110-265V	250W	90lm/w	80	0.9	120°	65	445x335x46

03 www.runnin.com